



CONTENTO™ SOLID SURFACE BATH & SINK

In Italy, people say *sono contento* to express happiness. It's the way you will feel about the artful shape, uncompromised bathing well, and blissful soaking experience of the Jacuzzi® Contento™ Solid Surface bath.

Pairing the Contento™ sink with the bath ups the dramatic appeal of the smooth, convex shapes on each vessel.



CONTENTO™ SOLID SURFACE BATHTUB & SINK



HIGH STYLE, ENDURING QUALITY



PRISTINE FINISH



INSULATING PROPERTIES



FEATURES

- Durable Luxecast® solid surface material comprised of mineral composite
- Easy-to-clean, non-porous white matte or gloss finish that resists bacteria and stains
- Integral linear overflow drain nestled inside the wall of the bath
- Insulating properties help keep the bath water warm
- Color- and texture-matched toe-tap drain kit included

BATH ACCESSORIES

- Lenire™ Luxury Pillow with Technogel® sold separately
- MZ20000 Drain Alignment Kit for freestanding bathtub installations sold separately
- View catalog for selection of floor-mount tub fillers

CONTENTO™ BATHTUB

Dimensions: 59" L x 32" W x 23" H

Bathing Depth: 20.25"

Bathtub Finishes: Matte or Gloss

Installation: Freestanding

Drain Location: Center

Certifications: IAPMO/cUPC

Warranty: 5-Year Limited Lifetime Warranty

Experiences:  Soaking Bath

CONTENTO™ SINK

Dimensions: 15.7" L x 12" W x 7" H

Installation: Vessel

Drain: Not included

Sink Finishes: Matte or Gloss

Certifications: IAPMO/cUPC

Warranty: 90-Day Limited Warranty



www.jacuzziluxurybath.com

13925 City Center Drive, Suite 200
Chino Hills, CA 91709 / U.S.A.
(800) 288-4002

©2018 Jacuzzi Inc. All rights reserved.
Jacuzzi® is a registered trademark of Jacuzzi Inc. All other brands, product names, company names, trade names and trademarks used are the property of their respective owners. Jacuzzi may add to, change or remove any part of these materials at any time, without notice. Reproduction in whole or in part without written permission is prohibited. International products may be configured differently to meet local electrical requirements. Dimensions are approximate.
01/18